


WIRELESS ROCKER SWITCH TRANSMITTER & COVER PLATE

WWS2-EN3

EnOcean® Enabled Wireless Wall Switch Transmitter Switch, 902 MHz

Includes Cover Plate.



SPECIFICATIONS

Operating Modes: On/Off, Toggle, Scene control
Power Supply: Powered by finger press (Electrodynamical Energy Harvester)

Frequency: 902 MHz

Antenna: Integrated antenna, 6.4 cm

Transmission Power: Max. 10mW EIRP

Energy Bowtravel/Operating Force: 50,000 actuations tested to EN60669 / VDE 0632

Operating Temperature: -25 to 65° C

Relative Humidity: 5 to 92% (noncondensing)

Dimensions: 2.75" x 4.50" x 0.8"

Approvals: RoHS

Agency Compliance:

- Switch
 - FCC ID: SZV-PTM210U
 - IC: 5713A-PTM210U
- Barrier Plate
 - Certified to UL514D
 - CSA C22.2 #42-1-13

Notes:

- Control one load or one group of loads with a single rocker style Wireless Switch Transmitter.
- **Typical range: 50-150 ft.**
 - Open area transmission could be farther. Consult factory for more information.
- **Mounting**
 - Includes barrier plate and mounts to electrical wall boxes (screws included).
 - Alternate surface mount accessory AWSTFM to install on any surface using double sided tape or Velcro™ (sold separately).
- For use with EN3 Series Relays.
- EEP F6-02-02