


WIRELESS ROCKER SWITCH TRANSMITTER & COVER PLATE

WWS2-EN3

EnOcean® Enabled Wireless Wall Switch
Transmitter Switch, 902 MHz

Includes Cover Plate.



SPECIFICATIONS

Operating Modes: On/Off, Toggle, Scene control
Power Supply: Powered by finger press
(Electrodynamic Energy Harvester)

Frequency: 902 MHz
Antenna: Integrated antenna, 15cm

Transmission Power: Max. 10mW EIRP

Energy Bowtravel/Operating Force: 50,000 actuations tested to
EN60669 / VDE 0632

Operating Temperature: -25 to 65° C

Relative Humidity: 5 to 92% (noncondensing)

Dimensions: 2.75" x 4.50" x 0.8"

Weight: 3 oz.

Agency Compliance:

- Switch
FCC ID: SZV-PTM210U
IC: 5713A-PTM210U
- Barrier Plate
Certified to UL514D
CSA C22.2 #42-1-13

Shipping Weight: 0.288 lbs.

Notes:

- Control one load or one group of loads with a single rocker style Wireless Switch Transmitter.
- **Typical range: 50-150 ft.**
 - **Open area transmission could be farther. Consult factory for more information.**
- **Mounting**
 - **Includes barrier plate and mounts to electrical wall boxes (screws included).**
 - **Alternate surface mount accessory AWSTFM to install on any surface using double sided tape or Velcro™ (sold separately).**
- For use with EN3 Series Relays.
- EEP F6-02-02