

ACCESSORIES


SUB-PANELS

Product Selection Guide. For full product information, see our website.

MODEL #	USE WITH ENCLOSURE	MATERIAL	HEIGHT	WIDTH	THICKNESS	MOUNTING AREA	SHIPPING WEIGHT
SP3303	MH3300 or MH3300K	Polymetal	11.330"	11.400"	.130"	129.16 square inches	0.847 lb.
SP3304	MH3300 or MH3300K	Perforated Steel	11.330"	11.400"	.250"	129.16 square inches	1.662 lb.
SP3803S	MH3800	Polymetal	19.000"	11.750"	.130"	223.25 square inches	1.705 lb.
SP3803L	MH3800	Polymetal	23.000"	11.750"	.130"	270.25 square inches	2.140 lb.
SP3804S	MH3800	Perforated Steel	19.000"	11.750"	.250"	223.25 square inches	2.940 lb.
SP3804L	MH3800	Perforated Steel	23.000"	11.750"	.250"	270.25 square inches	3.520 lb.
SP4403L	MH4400	Polymetal	16.875"	15.750"	.130"	265.78 square inches	2.100 lb.
SP4404L	MH4400	Perforated Steel	16.875"	15.750"	.250"	265.78 square inches	3.415 lb.
SP5503L	MH5500	Polymetal	23.000"	22.500"	.130"	517.50 square inches	3.940 lb.
SP5504L	MH5500	Perforated Steel	23.000"	22.500"	.250"	517.50 square inches	6.560 lb.
SP5803L	MH5800	Polymetal	34.125"	22.500"	.130"	767.81 square inches	5.875 lb.
SP5804L	MH5800	Perforated Steel	34.125"	22.500"	.250"	767.81 square inches	9.720 lb.

MOUNTING SUPPLIES

Product Selection Guide. For full product information, see our website.

MODEL #		WIDTH	LENGTH	TRACK TYPE	DISTANCE BETWEEN HOLE CENTERS
MT212-2	•	2.75"	2.00"	Screw mounted snap-in track	2.00" Center to Center
MT212-4	•	2.75"	4.00"	Screw mounted snap-in track	2.00" Center to Center
MT212-6	•	2.75"	6.00"	Screw mounted snap-in track	2.00" Center to Center
MT212-8	•	2.75"	8.00"	Screw mounted snap-in track	2.00" Center to Center
MT212-12	•	2.75"	12.00"	Screw mounted snap-in track	2.00" Center to Center
MT212-18	•	2.75"	18.00"	Screw mounted snap-in track	2.00" Center to Center
MT212-24	•	2.75"	24.00"	Screw mounted snap-in track	2.00" Center to Center
MT212-48	•	2.75"	48.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-2	•	4.00"	2.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-4	•	4.00"	4.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-6	•	4.00"	6.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-8	•	4.00"	8.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-10	•	4.00"	10.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-12	•	4.00"	12.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-18	•	4.00"	18.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-24	•	4.00"	24.00"	Screw mounted snap-in track	2.00" Center to Center
MT4-48	•	4.00"	48.00"	Screw mounted snap-in track	2.00" Center to Center
AT4-2	•	4.00"	2.00"	AdapTrack® for DIN rail	3 Most Common for AT4 Series #
AT4-6	•	4.00"	6.00"	AdapTrack® for DIN rail	3 Most Common for AT4 Series #
AT4-12	•	4.00"	12.00"	AdapTrack® for DIN rail	3 Most Common for AT4 Series #
AT4-24	•	4.00"	24.00"	AdapTrack® for DIN rail	3 Most Common for AT4 Series #
AT4-48	•	4.00"	48.00"	AdapTrack® for DIN rail	3 Most Common for AT4 Series #
ADIN35		35 mm	7.5 mm	Perforated DIN rail	25 mm Center to Center

 = UL Component Recognized ; USA & Canada

= 32 mm x 15 mm asymmetrical DIN rail EN50035; 35 mm x 7.5 mm symmetrical DIN rail EN50022; 22.4 mm x 6.9 mm symmetrical NEMA A Series rail

For full product information, see data sheets on website. Shipping weights are approximate and may change due to packaging options.

ACCESSORIES

REPLACEMENT & MISCELLANEOUS PARTS

Product Selection Guide. For full product information, see our website.

MODEL #	DESCRIPTION	FOR USE WITH MODEL(S)
ADIN35ES	Pair of End Stops for 35mm DIN Rail	ADIN35
APS53-TC	Primary voltage terminal cover	Functional Devices 300 VA and 500 VA power supplies
AR24D	Replacement relays (3-pack)	RIBR24D, RIBR24SD
ARL1C	Replacement relays (3-pack)	RIBRL1C, RIBRL1S, RIBRXLCA, RIBRXLCF, RIBRXLSA
AWSTFM	Flush surface mount backplate kit	WWS2-EN3
AXG	Split ring remote current sensor assembly (Wire Output)	RIBXJA, RIBXJF, RIBXLCJA, RIBXLCJF, RIBXLSJA, RIBXLSJF
AXGT	Split ring remote current sensor assembly (Terminal Output)	RIBXJA, RIBXJF, RIBXLCJA, RIBXLCJF, RIBXLSJA, RIBXLSJF
AXK	Remote mini current sensor assembly (Wire Output)	RIBXLCRA, RIBXLCRF, RIBXLSRA, RIBXLSRF, RIBXRA, RIBXRF
AXKT	Remote mini current sensor assembly (Terminal Output)	RIBXLCRA, RIBXLCRF, RIBXLSRA, RIBXLSRF, RIBXRA, RIBXRF
DS80625	No. 8 x 5/8" Self-Tapping Drill Screws	Functional Devices polymetal sub-panels
KEYSET	One set of 2 keys	Functional Devices key latch metal enclosures
MKL-1	Locking key latch assembly	Functional Devices metal enclosures except MH3300K
MKL-2	Locking key-hook latch assembly	Functional Devices MH3300K metal enclosures
MKL-3	Metal locking key latch assembly	Functional Devices metal enclosures except MH3300K
MKL-4	Coin locking key latch assembly	Functional Devices metal enclosures except MH3300K
TS-AN	Pluggable terminal strips	RIBAN12C, RIBAN24C

 = UL Component Recognized ; USA & Canada

= 32 mm x 15 mm asymmetrical DIN rail EN50035; 35 mm x 7.5 mm symmetrical DIN rail EN50022; 22.4 mm x 6.9 mm symmetrical NEMA A Series rail

For full product information, see data sheets on website. Shipping weights are approximate and may change due to packaging options.