

LATCHING RELAYS

RELAYS

ENCLOSED LATCHING RELAYS

Product Selection Guide. For full product information, see our website.

MODEL #	UL	COIL VOLTAGE	RELAY CONTACTS	CONTACT RATINGS			OVERRIDE SWITCH	AUXILIARY OUTPUT	HOUSING STYLE *	SHIPPING WEIGHT
		AC/DC		RESISTIVE	MOTOR	PILOT DUTY				
RIBL12B	•	12	1 SPST	20 A @ 120-277 Vac	3 HP @ 240 Vac	720 VA @ 120-277 Vac			A	0.420 lb.
RIBL12SB	•	12	1 SPST	20 A @ 120-277 Vac	3 HP @ 240 Vac	720 VA @ 120-277 Vac	•		A	0.420 lb.
RIBL12BM	•	12	1 SPST	20 A @ 120-277 Vac	3 HP @ 240 Vac	720 VA @ 120-277 Vac		•	B	0.490 lb.
RIBL12SBM	•	12	1 SPST	20 A @ 120-277 Vac	3 HP @ 240 Vac	720 VA @ 120-277 Vac	•	•	B	0.490 lb.
RIBL24B	•	24	1 SPST	20 A @ 120-277 Vac	3 HP @ 240 Vac	720 VA @ 120-277 Vac			A	0.420 lb.
RIBL24SB	•	24	1 SPST	20 A @ 120-277 Vac	3 HP @ 240 Vac	720 VA @ 120-277 Vac	•		A	0.420 lb.
RIBL24BM	•	24	1 SPST	20 A @ 120-277 Vac	3 HP @ 240 Vac	720 VA @ 120-277 Vac		•	B	0.600 lb.
RIBL24SBM	•	24	1 SPST	20 A @ 120-277 Vac	3 HP @ 240 Vac	720 VA @ 120-277 Vac	•	•	B	0.592 lb.

UL = UL Listed : UL916 Energy Management, UL864 Fire ; USA & Canada

* = See Housing Guide on pages 86-87

For full product information, see data sheets on website. Shipping weights are approximate and may change due to packaging options.

QR25723 03132019