

TRANSFORMERS

US MANUFACTURED TRANSFORMERS

- 40 VA through 96 VA
- Single and dual hub
- Foot or hub mountable
- Circuit breaker models
- Class 2 UL Listed
- 24 Vac secondary
- Single and multi-tap primaries



US MANUFACTURED TRANSFORMERS: 40-96 VA

MODEL #	MADE IN USA	UL	VA RATING	STYLE	OVER CURRENT PROTECTION	CLASS 2	PRIMARY VOLTAGE (VAC)	SEC. VOLTAGE (VAC)	FOOT MOUNT	HUBS	L	W	H	A	B	C	SHIPPING WEIGHT
TR40VA001US	•	•	40VA	1	Inherent	•	120	24	•	1 Threaded	2.380"	2.200"	2.930"	1.720"	1.750"	.980"	1.770 lb.
TR40VA002US	•	•	40VA	4	Inherent	•	120	24	•	2 Threaded	2.380"	2.200"	2.920"	1.720"	1.750"	.980"	1.780 lb.
TR50VA001US	•	•	50VA	1	Fuse	•	120	24	•	1 Threaded	2.750"	2.200"	2.910"	2.060"	1.750"	1.330"	2.200 lb.
TR50VA005US	•	•	50VA	2	Circuit Brkr.	•	120	24	•	1 Threaded	3.270"	2.525"	3.250"	2.210"	2.000"	1.130"	2.668 lb.
TR50VA022US	•	•	50VA	5	Circuit Brkr.	•	480/277/240/208/120	24	•	2 Threaded	3.260"	2.525"	3.290"	2.190"	2.000"	1.120"	2.760 lb.
TR100VA001US	•	•	96VA	2	Circuit Brkr.	•	120	24	•	1 Threaded	3.780"	2.500"	3.290"	2.740"	2.000"	1.630"	3.570 lb.
TR100VA002US	•	•	96VA	5	Circuit Brkr.	•	120	24	•	2 Threaded	3.750"	2.500"	3.290"	2.690"	2.000"	1.600"	3.600 lb.
TR100VA009US	•	•	96VA	5	Circuit Brkr.	•	480/277/240/208/120	24	•	2 Threaded	3.500"	2.500"	3.250"	2.720"	2.000"	1.630"	3.732 lb.

UL = UL Listed : UL5085-2 or UL5085-3 ; USA & Canada

For full product information, see data sheets on website. Shipping weights are approximate and may change due to packaging options.