


WIRELESS ROCKER SWITCH TRANSMITTER WITH COVER PLATE

FDLTS2

EnOcean 902 MHz Wireless Wall Transmitter Switch with Barrier and Cover Plate, White



SPECIFICATIONS

Operating Modes: On/Off, Toggle, Scene control
Power Supply: Powered by finger press (Electrodynamic Energy Harvester)

Frequency: 902 MHz
Antenna: Integrated antenna, 6.4cm

Transmission Power: Max. 10mW EIRP

Energy Bowtravel/Operating Force: 50,000 actuations tested to EN60669 / VDE 0632

Operating Temperature: -25 to 65° C

Relative Humidity: 5 to 92% (noncondensing)

Dimensions: 4.50" H x 2.75" W x 0.8" D

Agency Compliance:

- Switch
 FCC ID: SZV-PTM210U
 IC: 5713A-PTM210U
- Barrier Plate
 Certified to UL514D
 CSA C22.2 #42-1-13

Notes:

- Control one load or one group of loads with a single rocker style Wireless Switch Transmitter.
- Typical range: 50-150 ft.
 - Open area transmission could be farther. Consult factory for more information.
- Mounting
 - Includes barrier plate and mounts to electrical wall boxes (screws included).
 - Alternate surface mount accessory AWSTFM to install on any surface using double sided tape or Velcro™ (sold separately).
- For use with FDLR Series Relays, FDLR20GV and FDLR05BPD dimmers
- EEP F6-02-02