RIBMU1SM-250
RIBMH1SM-250

LED ON = RELAY ACTIVATED

Bulletin B1407 • 393160B

c UL us LISTED

TYPE F, G, EM
For use with
Smoke Control System
General Signaling System
Equip. NM

RIB Functional Devices, Inc.™

SWITCH STATUS

Closed
Common
Auto

COIL

Common
10-30Vac/dc
120Vac or 208-277Vac

CONTACT RATINGS

15 Amp Resistive @ 125Vac
10 Amp Resistive @ 250Vac
345 VA Pilot Duty @ 120/240Vac (N/O)
211 VA Pilot Duty @ 120/240Vac (N/C)
1/3 HP for N/O @ 120-240Vac
1/6 HP for N/C @ 120-240Vac

COIL RATINGS

20 mA @ 10-30 Vdc
55 mA @ 10-30 Vac
28 mA @ 120 Vac
39 mA @ 208-277 Vac

FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F)

Connect Yellow Jumper Wire to N/O or N/C

N/C N/O



CONTACTS

Relay Contacts

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBMU1SM-250 RIBMH1SM-250 LED ON = RELAY ACTIVATED Bulletin B1407 • 393160B c UL us LISTED TYPE F, G, EM For use with Smoke Control System General Signaling System Equip. NM RIB Functional Devices, Inc.™ SWITCH STATUS Closed Common Auto COIL Common 10-30Vac/dc 120Vac or 208-277Vac CONTACT RATINGS 15 Amp Resistive @ 125Vac 10 Amp Resistive @ 250Vac 345 VA Pilot Duty @ 120/240Vac (N/O) 211 VA Pilot Duty @ 120/240Vac (N/C) 1/3 HP for N/O @ 120-240Vac 1/6 HP for N/C @ 120-240Vac COIL RATINGS 20 mA @ 10-30 Vdc 55 mA @ 10-30 Vac 28 mA @ 120 Vac 39 mA @ 208-277 Vac FOR SUPPLY CONNECTIONS USE #14 AWG OR LARGER WIRES RATED AT LEAST 75°C (167°F) Connect Yellow Jumper Wire to N/O or N/C N/C N/O



CONTACTS Relay Contacts CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE RE-QUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.