


DC POWER SUPPLY

PSH100AB10-DC

Enclosed Single Switching DC Power Supply, 120 to 24 Vdc @ 2.5 Amp, Class 2



* Move internal jumper to "HOT" position if you wish outlets to always be hot otherwise outlets will be switched by main breaker.

SPECIFICATIONS

Over Current Protection: Circuit Breaker
Frequency: 50/60 Hz
24 Vdc ON/OFF: On / Off Switch & Breaker
Main Breaker ON/OFF: Switch / Breaker (10 Amp) (Kills power to entire unit: Outlets, Aux. Output, & Transformer)*
 Total Combined Output 9A
Max. Ambient Temperature: 40° C
Approvals: Class 2 (UL Approved UL5085-3), UL508, C-UL, CE, RoHS, FCC
Dimensions: 4.500" H x 5.438" W x 4.500" D
Origin: Made of US and non-US parts

Input Wires: Input Power Wires
 BLK: 120 Vac
 WHT: Neutral
 GRN: Ground

Outlet Wires
 BLK: 120 Vac
 WHT: Neutral
 GRN: Ground

Output Wires: Auxiliary Output
 BLU: 120 Vac

Notes:
 • Output derating may exceed 20% due to elevated ambient temperature or heat buildup in device over time.