RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output

Bulletin B1251 • 393122A

UL508 UL864

Functional Devices, Inc.

www.FunctionalDevices.com

LOAD WIRE

Optional mounting tab may be removed.

Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

MAX OUTPUT CURRENT ACCURACY

99% FS (20%-100% Span) 30mA LINEARITY

18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output Bulletin B1251 • 393122A

Optional mounting tab may be removed.

UL508 UL864

Functional

www.FunctionalDevices.com LOAD WIRE

 Racheting Cam may be closed against load wire to secure RIBXG420-20 in position. MAX OUTPUT CURRENT

99% FS (20%-100% Span) 30mA

WIRES **LINEARITY** 18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

UL508



RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output

Bulletin B1251 • 393122A

UL864

Functional Devices, Inc.

www.FunctionalDevices.com LOAD WIRE

Optional mounting tab may be removed.

WIRFS

ACCURACY

Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

<u>ACCURACY</u> MAX OUTPUT CURRENT 99% FS (20%-100% Span)

LINEARITY 18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output

Bulletin B1251 • 393122A

99% FS (20%-100% Span)

Ontional mounting tab may be removed.

UL508 UL864



www.FunctionalDevices.com

LOAD WIRE

MAX OUTPUT CURRENT 30mA

Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

WIRES **LINEARITY**

18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

UL508

UL864

RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output Bulletin B1251 • 393122A

Functional Devices, Inc.

www.FunctionalDevices.com

LOAD WIRE

Optional mounting tab may be removed.

Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

ACCURACY MAX OUTPUT CURRENT 99% FS (20%-100% Span) 30mA WIRES LINEARITY

18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-20 Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output

Bulletin B1251 • 393122A

 Optional mounting tab may be removed. • Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

MAX OUTPUT CURRENT **ACCURACY** 99% FS (20%-100% Span) 30mA

WIRES **LINEARITY**

18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REOUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

UL508

UL864

UL508

UL864

RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output

Bulletin B1251 • 393122A

Optional mounting tab may be removed.

Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

ACCURACY MAX OUTPUT CURRENT 99% FS (20%-100% Span) 30mA WIRES

LINEARITY 18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REOUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

UL508

UL864

RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output

Bulletin B1251 • 393122A

 Optional mounting tab may be removed. Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

ACCURACY MAX OUTPUT CURRENT

99% FS (20%-100% Span) WIRES LINEARITY

18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

UL508

UL864

MAX OUTPUT CURRENT

RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output

Bulletin B1251 • 393122A

Ontional mounting tab may be removed.

Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

ACCURACY 99% FS (20%-100% Span) 30mA

WIRES LINEARITY 18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-20

Enclosed 20A Current Sensor w/ Loop Powered 4-20mA Transmitter Output

Bulletin B1251 • 393122A

UL508 UL864



www.FunctionalDevices.com LOAD WIRE

· Optional mounting tab may be removed.

Racheting Cam may be closed against load wire to secure RIBXG420-20 in position.

ACCURACY MAX OUTPUT CURRENT 99% FS (20%-100% Span) 30mA

WIRES LINEARITY 18AWG, 600V Rated 99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.






Functional

LOAD WIRE





















Functional

Devices, Inc.

LOAD WIRE

www.FunctionalDevices.com

